




List 7173

EXOCARB® DIAMOND LS-BN, Long Shank

SPEED FEED 1383	CARBIDE	DIA	12µm	30°			SHANK h6	STUB	PACKED 1 PIECE
---------------------------	----------------	------------	-------------	------------	--	--	--------------------	-------------	--------------------------

Radius Tolerance	
0.5mm ≤ D ≤ 12mm	+0 / -0.015mm



EDP Number		Diameter		Length of Cut		Neck Length		Neck Diameter		Overall Length		Shank Diameter		Number of Flutes
		D (mm)	Lc (mm)	L1 (mm)	d1 (mm)	L (mm)	d (mm)							
71730116	●	0.50	0.50	2.50	0.48	50.00	3.00	2						
71730216	●	1.00	1.00	5.00	0.96	60.00	3.00	4						
71730316	●	1.50	1.50	7.50	1.43	75.00	3.00	4						
71730416	●	2.00	2.00	10.00	1.90	75.00	3.00	4						
71730516	●	3.00	3.00	15.00	2.85	75.00	3.00	4						
71730616	●	4.00	4.00	20.00	3.80	75.00	4.00	4						
71730716	●	6.00	6.00	30.00	5.70	100.00	6.00	4						
71730816	●	8.00	8.00	32.00	7.60	100.00	8.00	4						
71730916	●	10.00	10.00	40.00	9.50	125.00	10.00	4						
71731016	●	12.00	12.00	48.00	11.40	150.00	12.00	4						

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

HTE

P					M			K	N				S		Other	
Steel					Stainless Steel			Cast Iron	Non-Ferrous				HRSA		Graphite	Cobalt-Chrome
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Mg		Brass, Bronze	Nickel Alloy	Titanium					
Low	Medium	High			6061	7075						Inconel	6Al4V (30 HRC)			
1010	1035	1065	4140	4340	300	400	17-4 PH	6061	7075	Casting						
									○	○					○	

○ Good ○ Best

