


List 7231

EXOCARB® DIAMOND DIA-LN-EBM, Long Reach, High Precision

SPEED FEED 1492	CARBIDE	DIA	12µm	30°		SHANK h6	REG	LONG	EXTRA LONG	PACKED 1 PIECE
---------------------------	----------------	------------	-------------	------------	--	--------------------	------------	-------------	-------------------	--------------------------

Radius Tolerance	
1/64" ≤ D ≤ 1/8"	+0 / -0.0004"
3/16" ≤ D ≤ 1/4"	+0 / -0.0007"



EDP Number	Diameter	Length of Cut	Neck Length	Neck Diameter	Overall Length	Shank Diameter	Number of Flutes	
								D (Fractional Size)
72310116	●	1/64	0.047	0.160	0.012	1.500	0.125	2
72310216	●	1/32	0.094	0.310	0.027	1.500	0.125	4
72310316	●	3/64	0.188	0.470	0.043	1.500	0.125	4
72310416	●	1/16	0.188	0.630	0.058	1.500	0.125	4
72310516	●	3/32	0.375	0.940	0.088	2.000	0.125	4
72310616	●	1/8	0.750	1.500	0.120	3.000	0.125	4
72310716	●	3/16	0.750	1.880	0.183	4.000	0.188	4
72310816	●	1/4	1.000	2.500	0.245	4.000	0.250	4

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N			S		Other		
Steel					Stainless Steel			Cast Iron	Non-Ferrous			HRSA		Graphite	Cobalt-Chrome	
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Mg	Brass, Bronze	Nickel Alloy			Titanium
Low	Medium	High							Inconel	6Al4V (30 HRC)						
1010	1035	1065	4140	4340				6061	7075	Casting						
1018	1045							○	○					○		

○ Good ○ Best

