



EXOCARB® DG-EML

Long Length of Cut DG Coated 4-Fluted Square End Mills for Graphite

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

List 7440

EXOCARB® DG-EML

NEW

SPEED FEED
1384

CARBIDE

DG

4 FLUTE

30°



SHANK
h4

LONG

PACKED
1 PIECE

Radius Tolerance	
1/32" ≤ D ≤ 3/16"	+/- 0.00028"
1/4" ≤ D ≤ 1/2"	+/- 0.00039"



EDP Number		Diameter		Length of Cut	Overall Length	Shank Diameter
		D (Fractional Size)	Lc (Inch)	L (Inch)	d (Inch)	
74400125	○	1/32	0.156	2.500	0.125	
74400225	○	3/64	0.234	2.500	0.125	
74400325	●	1/16	0.313	2.500	0.125	
74400425	●	3/32	0.469	2.500	0.125	
74400525	●	1/8	0.625	3.000	0.125	
74400625	●	3/16	0.938	3.000	0.188	
74400725	●	1/4	1.250	4.000	0.250	
74400825	●	3/8	1.875	6.000	0.375	
74400925	●	1/2	2.250	6.000	0.500	

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N			S		Other	
Steel					Stainless Steel			Cast Iron	Non-Ferrous			HRSA		Graphite	Cobalt-Chrome
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Mg	Brass, Bronze	Nickel Alloy		
Low	Medium	High			300	400	17-4 PH	6061 7075	Casting	Inconel				6Al4V (30 HRC)	
1010	1035	1065	4140	4340											
1018	1045														

○ Good ○ Best

