



List 7441

EXOCARB® DG-LN-EML

NEW

SPEED FEED
1385

CARBIDE

DG

4 FLUTE

30°



SHANK
h4

LONG

PACKED
1 PIECE



Radius Tolerance	
1/32" ≤ D ≤ 3/16"	+/- 0.00028"
D = 1/4"	+/- 0.00039"

EDP Number		Diameter		Length of Cut	Neck Length	Overall Length	Shank Diameter
		D (Fractional Size)	Lc (Inch)	L1 (Inch)	L (Inch)	d (Inch)	
74410125	○	1/32	0.156	0.250	2.500	0.125	
74410225	○	3/64	0.234	0.500	2.500	0.125	
74410325	○	1/16	0.313	0.625	2.500	0.125	
74410425	○	3/32	0.469	1.000	2.500	0.125	
74410525	●	1/8	0.625	1.250	3.000	0.125	
74410625	●	3/16	0.938	1.500	3.000	0.188	
74410725	●	1/4	1.250	2.000	4.000	0.250	

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N			S		Other		
Steel					Stainless Steel			Cast Iron	Non-Ferrous			HRSA		Graphite	Cobalt-Chrome	
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Mg	Brass, Bronze	Nickel Alloy			Titanium
Low	Medium	High							Inconel	6Al4V (30 HRC)						
1010	1035	1045	1065	4140	4340			6061	7075	Casting						
1018	1045	1065														

○ Good ⊙ Best

