



List 7471

EXOCARB® DG-LN-CR-EML

NEW	SPEED FEED 1456	CARBIDE	DG	4 FLUTE	30°	SHANK h4	LONG	PACKED 1 PIECE
------------	---------------------------	----------------	-----------	----------------	------------	--------------------	-------------	--------------------------

Cutting Diameter Tolerance	
1/32" ≤ D ≤ 3/16"	+/- 0.00028"
D = 1/4"	+/- 0.00039"



EDP Number	Diameter	Corner Radius	Length of Cut			Overall Length	Shank Diameter
			D (Fractional Size)	R (Inch)	Lc (Inch)		
74710125	1/32	0.005	0.156	0.250	2.500	0.125	
74710225	3/64	0.010	0.234	0.500	2.500	0.125	
74710325	1/16	0.010	0.313	0.625	2.500	0.125	
74710425	3/32	0.015	0.469	1.000	2.500	0.125	
74710525	3/32	0.020	0.469	1.000	2.500	0.125	
74710625	1/8	0.015	0.625	1.250	3.000	0.125	
74710725	1/8	0.020	0.625	1.250	3.000	0.125	
74710825	1/8	0.030	0.625	1.250	3.000	0.125	
74710925	3/16	0.030	0.938	1.500	3.000	0.188	
74711025	3/16	0.060	0.938	1.500	3.000	0.188	
74711125	1/4	0.015	1.250	2.000	4.000	0.250	
74711225	1/4	0.020	1.250	2.000	4.000	0.250	
74711325	1/4	0.030	1.250	2.000	4.000	0.250	
74711425	1/4	0.060	1.250	2.000	4.000	0.250	

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N			S		Other	
Steel					Stainless Steel			Cast Iron	Non-Ferrous			HRSA		Graphite	Cobalt-Chrome
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Mg		Brass, Bronze	Nickel Alloy	Titanium				
Low	Medium	High			6061	7075						Inconel	6Al4V (30 HRC)		
1010	1035	1065	4140		300	400	17-4 PH								
1018	1045		4340						Casting						

○ Good ⊙ Best

