




List 7530

EXOPRO AERO-S, High Helix

SPEED FEED 325	CARBIDE	DIA	2 FLUTE	JOBBER	40°	SHANK h6	PACKED 1 PIECE
-------------------	---------	-----	---------	--------	-----	-------------	-------------------

Cutting Diameter Tolerance
inch
+0 / -0.001



EDP Number		Diameter (D)					Flute Length	Overall Length	Shank Diameter
		Fractional Size	Wire Gage	Letter Size	mm	Inch	FL (mm)	L (mm)	d (mm)
753009816	●	-	40	-	2.502	0.09850	15.20	50.80	2.50
753012916	●	-	30	-	3.277	0.12900	20.30	76.20	3.27
753016116	●	-	20	-	4.102	0.16150	25.40	101.60	4.10
753019116	●	-	11	-	4.864	0.19150	27.90	101.60	4.86
753022116	●	-	2	-	5.626	0.22150	33.00	101.60	5.62
753025116	●	1/4	-	-	6.375	0.25000	38.10	101.60	6.37
753031316	●	5/16	-	-	7.963	0.31250	48.20	101.60	7.96
753037616	●	3/8	-	-	9.550	0.37500	58.40	152.40	9.55
753043816	●	7/16	-	-	11.138	0.43750	66.00	152.40	11.13
753050116	●	1/2	-	-	12.725	0.50000	76.20	152.40	12.72

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked
Note: Drills are oversize over nominal.



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

Carbon Fiber (CFRP)	Glass Fiber (GFRP)	Aramid Fiber (AFRP)	Honeycomb					Carbon/Carbon	Carbon Fiber/Aluminum Stack	Carbon Fiber/Titanium Stack	Carbon Fiber/Al/Ti/CRES Stack
			CFRP/Nomex	GFRP/Nomex	AFRP	CFRP/Al	Al/Al				
○	○		○	○		○	○		○		

○ Good ○ Best

