



List 78008



OSG PHOENIX[®] PHC BORE

SPEED FEED 1534-1535	INSERTS 1246	ACCS. 1247	STEEL	PACKED 1 PIECE
--------------------------------	------------------------	----------------------	--------------	--------------------------



EDP Number	Designation	Type	Diameter		Number of Flutes	Body Height		Flange Diameter		Bore Diameter		Keyway Width		Keyway Depth		Applicable Insert
			D (Inch)	D1 (Inch)		H (Inch)	D2 (Inch)	d3 (Inch)	a (Inch)	b (Inch)						
7800802	● PHC12R200A075-4	2	2.000	1.346	4	1.968	1.850	0.750	0.315	0.197	SXMT12					
7800800	● PHC09R200A075-5	2	2.000	1.535	5	1.968	1.850	0.750	0.315	0.197	SDMT09					
7800803	● PHC12R250A075-5	2	2.500	1.846	5	1.968	2.362	0.750	0.315	0.197	SXMT12					
7800807	● PHC12R250A075-4	2	2.500	1.846	4	1.968	2.362	0.750	0.315	0.197	SXMT12					
7800801	● PHC09R250A075-6	2	2.500	2.035	6	1.968	2.362	0.750	0.315	0.197	SDMT09					
7800804	● PHC12R300A100-7	2	3.000	2.346	7	2.480	2.835	1.000	0.375	0.236	SXMT12					
7800808	● PHC12R300A100-5	2	3.000	2.346	5	2.480	2.835	1.000	0.375	0.236	SXMT12					
7800806	● PHC09R300A100-8	2	3.000	2.535	8	2.480	2.835	1.000	0.375	0.236	SDMT09					
7800805	● PHC12R400A150-8	3	4.000	3.346	8	2.480	3.779	1.500	0.625	0.394	SXMT12					
7800809	● PHC12R400A150-6	3	4.000	3.346	6	2.480	3.779	1.500	0.625	0.394	SXMT12					
7800810	● PHC12R500A150-10	3	5.000	4.346	10	2.480	3.779	1.500	0.625	0.394	SXMT12					
7800811	● PHC12R600A150-12	3	6.000	5.346	12	2.480	3.779	1.500	0.625	0.394	SXMT12					

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



DESIGNATION EXPLANATION

PHC 09 R 200 A 075-5



See Full Detail on Page 1524

P	M	K	N	S	H
Steel	Stainless Steel	Cast Iron	Non-Ferrous	HRSA	Hardened Steel
○	○	○		○	○

Material recommendation based on inserts compatible with this tool body.

○ Good ○ Best

