





List 7808H

OSG PHOENIX[®] PSE ACCESSORIES

PACKED	PACKED
1 PIECE	10 PIECE

Appearance	EDP No.		Designation	Applicable Insert	Applicable Cutter		Recommended Tightening Torque
					Inch	mm	
 Clamping Screw	7808098	●	FS18634P (M1.8 x 3.4, Torx 6IP)	ZDKT07	PSE SA/SF/ASF Ø0.375-0.500	PSE SS/SF Ø10-12	0.5 Nm
	7808099	●	FS18637P (M1.8 x 3.7, Torx 6IP)	ZDKT07	PSE SA/SF/ASF Ø0.625-1.250	PSE SS/SF Ø16-32	0.5 Nm
	7808107	●	FS25656P (M2.5 x 5.6, Torx 8IP)	ZD_T11	PSE SA/FA/ASF Ø0.625-1.250	PSE SS/SF Ø16-35	1.6 Nm
	7808109	●	FS25673P (M2.5 x 7.3, Torx 8IP)	ZD_T11	PSE BORE Ø2.000-3.000	PSE BORE Ø40-80	1.6 Nm
	7808115	●	FS35686P (M3.5 x 8.6, Torx 15IP)	ZDKT15	PSE SA/FA/ASF Ø1.000-1.500, PSE BORE Ø2.000-6.000	PSE SS/SF Ø25-63, PSE BORE Ø40-125	3.2 Nm
 Power Screw	7808150	●	PS0830 (M8x30)	-	-	PSE BORE Ø40	15.0 Nm
	7808151	●	PS1031 (M10x31)	-	-	PSE BORE Ø50	20.0 Nm
 Wrench	7808223	●	6IP-D (Torx 6IP)	ZDKT07	PSE SA/SF/ASF Ø0.375-1.250	PSE SS/SF Ø10-32	-
	7808225	●	8IP-D (Torx 8IP)	ZD_T11	PSE SA/FA/ASF Ø0.625-1.250, PSE BORE Ø2.000-3.000	PSE SS/SF Ø16-35, PSE BORE Ø40-80	-
	7808228	●	15IP-D (Torx 15IP)	ZDKT15	PSE SA/FA/ASF Ø1.000-1.500, PSE BORE Ø2.000-6.000	PSE SS/SF Ø25-63, PSE BORE Ø40-125	-

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: Wrench sold separately

Packed: Clamping Screws = 10 pcs.; Power Screw = 1 pc.; Wrench = 1 pc.

PXT

