




## List 78334

OSG PHOENIX<sup>®</sup> PMD SF, Screw Fit Head



<b>SPEED FEED</b> 1532-1533	<b>INSERTS</b> 1233-1236	<b>ACCS.</b> 1237	<b>STEEL</b>	<b>2 FLUTE</b>	<b>PACKED</b> 1 PIECE
--------------------------------	-----------------------------	----------------------	--------------	----------------	--------------------------




EDP Number	Designation	Dia.		Number of Effective Flutes	Pilot Dia.		Thread Size		Flange Dia.		Length of Cut		Drilling Depth		Overall Length	Spanner Wrench	Center Insert	Peripheral Insert
		D (mm)	Da (mm)		Da (mm)	Dg (mm)	D2 (mm)	Lc (mm)	l1 (mm)	L (mm)								
7803416	▲ PMD11R020SF10-1	20.00	10.50	1	M10	18.00	10.00	20.00	48.00	14	ZPNT10	ZDKT11						
7803417	▲ PMD11R025SF12-1	25.00	12.50	1	M12	23.00	10.00	25.00	48.00	17	ZPNT13	ZDKT11						
7803418	▲ PMD11R032SF16-1	32.00	17.00	1	M16	28.00	10.00	28.00	58.00	22	ZPNT17	ZDKT11						

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



## DESIGNATION EXPLANATION

**PMD 11 R 020 SF 10-1**



See Full Detail on Page 1524

P	M	K	N	S	H
Steel	Stainless Steel	Cast Iron	Non-Ferrous	HRSA	Hardened Steel
○	◎	◎	◎	◎	◎

Material recommendation based on inserts compatible with this tool body.

○ Good ◎ Best

