



List 78421

OSG PHOENIX® PZAG, Bore



SPEED FEED
370

INSERTS
298


ACCS.
299

STEEL




4 FLUTE

PACKED
1 PIECE



EDP Number	Designation	Diameter	Drilling Depth	Body Height	Flange Diameter	Bore Diameter	Keyway Width	Keyway Depth	Min. Drill Hole Size (in)	Max Stepover for Plunging	Applicable Insert
		D (in)	I1 (mm)	H (in)	D2 (in)	d3 (in)	a (in)	b (in)	Ar Max (in)		
7832111	▲ PZAG13R054M22-4	54.00	35.00	63.00	45.00	22.00	10.40	6.30	29.00	12.50	ZPNT13
7832112	▲ PZAG13R058M22-4	58.00	38.00	63.00	45.00	22.00	10.40	6.30	33.00	12.50	ZPNT13
7832113	▲ PZAG13R062M22-4	62.00	41.00	63.00	45.00	22.00	10.40	6.30	37.00	12.50	ZPNT13
7832114	▲ PZAG13R067M22-4	67.00	44.00	63.00	45.00	22.00	10.40	6.30	42.00	12.50	ZPNT13
7832115	▲ PZAG13R072M22-4	72.00	47.00	63.00	45.00	22.00	10.40	6.30	47.00	12.50	ZPNT13
7832116	▲ PZAG17R076M22-4	76.00	50.00	63.00	45.00	22.00	10.40	6.30	44.00	16.00	ZPNT17
7832117	▲ PZAG17R082M22-4	82.00	54.00	63.00	45.00	22.00	10.40	6.30	50.00	16.00	ZPNT17

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



DESIGNATION EXPLANATION

PZAG-13-R-054-M-22-4



See Full Detail on Page 360

P	M	K	N	S	H
Steel	Stainless Steel	Cast Iron	Non-Ferrous	HRSA	Hardened Steel
○	○	○	○	○	○

Material recommendation based on inserts compatible with this tool body.

○ Good ○ Best

