




## List 801

OSG Carbide Bur SA-Cylindrical

SPEED FEED 1518	CARBIDE	BR	STUB	REG	LONG	PACKED 1 PIECE
--------------------	---------	----	------	-----	------	-------------------



EDP Number		Diameter		Length of Cut		Overall Length		Shank Diameter		Style
		D (Fractional Size)	D (mm)	Lc (Inch)	Lc (mm)	L (Inch)	L (mm)	d (Inch)	d (mm)	
801-1250-60	●	-	3.00	-	12.00	-	56.00	-	6.00	SA-11M
801-1250-60-EC	●	-	3.00	-	12.00	-	56.00	-	6.00	SA-11M
801-1250	●	1/8	-	0.500	-	2.330	-	0.250	-	SA-11
801-1250-EC	●	1/8	-	0.500	-	2.330	-	0.250	-	SA-11
801-1875	●	3/16	-	0.625	-	2.000	-	0.250	-	SA-14
801-1875-EC	●	3/16	-	0.625	-	2.000	-	0.250	-	SA-14
801-1875-60	●	-	5.00	-	16.00	-	50.00	-	6.00	SA-14M
801-1875-60-EC	●	-	5.00	-	16.00	-	50.00	-	6.00	SA-14M
801-2362	●	-	6.00	-	16.00	-	50.00	-	6.00	SA-1M
801-2362-EC	●	-	6.00	-	16.00	-	50.00	-	6.00	SA-1M
801-2500	●	1/4	-	0.625	-	2.000	-	0.250	-	SA-1
801-2500-EC	●	1/4	-	0.625	-	2.000	-	0.250	-	SA-1
801-3125	●	5/16	-	0.750	-	2.750	-	0.250	-	SA-2
801-3125-EC	●	5/16	-	0.750	-	2.750	-	0.250	-	SA-2
801-3125-60	●	-	8.00	-	19.00	-	63.00	-	6.00	SA-2M
801-3125-60-EC	●	-	8.00	-	19.00	-	63.00	-	6.00	SA-2M
801-3750-60	●	-	9.50	-	19.00	-	63.00	-	6.00	SA-3M
801-3750-60-EC	●	-	9.50	-	19.00	-	63.00	-	6.00	SA-3M
801-3750	●	3/8	-	0.750	-	2.500	-	0.250	-	SA-3
801-3750-EC	●	3/8	-	0.750	-	2.500	-	0.250	-	SA-3
801-4375-60	●	-	11.00	-	25.00	-	63.00	-	6.00	SA-4M
801-4375-60-EC	●	-	11.00	-	25.00	-	63.00	-	6.00	SA-4M
801-4375	●	7/16	-	1.000	-	3.000	-	0.250	-	SA-4
801-4375-EC	●	7/16	-	1.000	-	3.000	-	0.250	-	SA-4
801-5000-60	●	-	12.70	-	25.00	-	69.00	-	6.00	SA-5M
801-5000-60-EC	●	-	12.70	-	25.00	-	69.00	-	6.00	SA-5M
801-5001-60	●	-	12.70	-	12.70	-	58.00	-	6.00	SA-5MF
801-5001-60-EC	●	-	12.70	-	12.70	-	58.00	-	6.00	SA-5MF
801-5001	●	1/2	-	0.500	-	2.500	-	0.250	-	SA-5F
801-5001-EC	●	1/2	-	0.500	-	2.500	-	0.250	-	SA-5F
801-5000	●	1/2	-	1.000	-	2.750	-	0.250	-	SA-5
801-5000-EC	●	1/2	-	1.000	-	2.750	-	0.250	-	SA-5
801-6250	●	5/8	-	1.000	-	2.750	-	0.250	-	SA-6
801-6250-EC	●	5/8	-	1.000	-	2.750	-	0.250	-	SA-6
801-6250-60	●	-	16.00	-	25.00	-	69.00	-	6.00	SA-6M
801-6250-60-EC	●	-	16.00	-	25.00	-	69.00	-	6.00	SA-6M
801-7501-60	●	-	19.00	-	25.00	-	69.00	-	6.00	SA-7M
801-7501-60-EC	●	-	19.00	-	25.00	-	69.00	-	6.00	SA-7M
801-7500	●	3/4	-	0.750	-	2.500	-	0.250	-	SA-16
801-7500-60	●	-	19.00	-	19.00	-	63.00	-	6.00	SA-16M
801-7500-60-EC	●	-	19.00	-	19.00	-	63.00	-	6.00	SA-16M
801-7500-EC	●	3/4	-	0.750	-	2.500	-	0.250	-	SA-16
801-7501	●	3/4	-	1.000	-	2.750	-	0.250	-	SA-7
801-7501-EC	●	3/4	-	1.000	-	2.750	-	0.250	-	SA-7
801-1000-60	●	-	25.00	-	25.00	-	69.00	-	6.00	SA-9M
801-1000	●	1	-	1.000	-	2.770	-	0.250	-	SA-9
801-1000-EC	●	1	-	1.000	-	2.770	-	0.250	-	SA-9
801-1000-60-EC	●	-	25.00	-	25.00	-	69.00	-	6.00	SA-9M

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: Tool diameter ≤ 1/4" / 6mm have brazed carbide shanks, all others have hardened steel shanks.



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

