



## List 802

OSG Carbide Bur SC-Cylindrical Ball End

<b>SPEED FEED</b> 1518	<b>CARBIDE</b>	<b>BR</b>	<b>STUB</b>	<b>REG</b>	<b>LONG</b>	<b>PACKED</b> 1 PIECE
---------------------------	----------------	-----------	-------------	------------	-------------	--------------------------



EDP Number		Diameter		Length of Cut		Overall Length		Shank Diameter		Style
		D (Fractional Size)	D (mm)	Lc (Inch)	Lc (mm)	L (Inch)	L (mm)	d (Inch)	d (mm)	
802-1250-60	●	-	3.00	-	12.00	-	56.00	-	6.00	SC-11M
802-1250	●	1/8	-	0.500	-	2.000	-	0.250	-	SC-11
802-1875	●	3/16	-	0.625	-	2.000	-	0.250	-	SC-14
802-1875-60	●	-	5.00	-	16.00	-	50.00	-	6.00	SC-14M
802-2362	●	-	6.00	-	16.00	-	50.00	-	6.00	SC-1M
802-2500	●	1/4	-	0.625	-	2.000	-	0.250	-	SC-1
802-3125	●	5/16	-	0.750	-	2.500	-	0.250	-	SC-2
802-3125-60	●	-	8.00	-	19.00	-	63.00	-	6.00	SC-2M
802-3750	●	3/8	-	0.750	-	2.500	-	0.250	-	SC-3
802-3750-60	●	-	9.50	-	19.00	-	63.00	-	6.00	SC-3M
802-4375-60	●	-	11.00	-	25.00	-	69.00	-	6.00	SC-4M
802-4375	●	7/16	-	1.000	-	2.750	-	0.250	-	SC-4
802-5000-60	●	-	12.70	-	25.00	-	69.00	-	6.00	SC-5M
802-5000	●	1/2	-	1.000	-	2.750	-	0.250	-	SC-5
802-6250	●	5/8	-	1.000	-	2.700	-	0.250	-	SC-6
802-6250-60	●	-	16.00	-	25.00	-	69.00	-	6.00	SC-6M
802-7500-60	●	-	19.00	-	25.00	-	69.00	-	6.00	SC-7M
802-7500	●	3/4	-	1.000	-	2.750	-	0.250	-	SC-7

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: Tool diameter ≤ 1/4" / 6mm have brazed carbide shanks, all others have hardened steel shanks.



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

