




## List 8120

EXOCARB® AERO CA-RG-EDS

<b>SPEED FEED</b> 1382	<b>CARBIDE</b>	<b>BR</b>	<b>2 FLUTE</b>	<b>30°</b>		<b>SHANK</b> h6	<b>STUB</b>	<b>REG</b>	<b>LONG</b>	<b>PACKED</b> 1 PIECE
---------------------------	----------------	-----------	----------------	------------	--	--------------------	-------------	------------	-------------	--------------------------

Cutting Diameter Tolerance	
1mm ≤ D ≤ 12mm	+0 / -0.020mm
13mm ≤ D ≤ 16mm	+0 / -0.030mm



EDP Number		Diameter		Length of Cut	Overall Length	Shank Diameter
		D (mm)	Lc (mm)	L (mm)	d (mm)	
8502010	●	1.00	2.50	40.00	4.00	
8502015	●	1.50	4.00	40.00	4.00	
8502020	●	2.00	6.00	40.00	4.00	
8502025	●	2.50	8.00	40.00	4.00	
8502030	●	3.00	8.00	45.00	6.00	
8502035	●	3.50	10.00	45.00	6.00	
8502040	●	4.00	11.00	45.00	6.00	
8502045	●	4.50	11.00	45.00	6.00	
8502050	●	5.00	13.00	50.00	6.00	
8502055	●	5.50	13.00	50.00	6.00	
8502060	●	6.00	13.00	50.00	6.00	
8502065	●	6.50	16.00	60.00	8.00	
8502070	●	7.00	16.00	60.00	8.00	
8502075	●	7.50	16.00	60.00	8.00	
8502080	●	8.00	19.00	60.00	8.00	
8502085	●	8.50	19.00	70.00	10.00	
8502090	●	9.00	19.00	70.00	10.00	
8502095	●	9.50	19.00	70.00	10.00	
8502100	●	10.00	22.00	70.00	10.00	
8502105	●	10.50	22.00	75.00	12.00	
8502110	●	11.00	22.00	75.00	12.00	
8502115	●	11.50	22.00	75.00	12.00	
8502120	●	12.00	26.00	75.00	12.00	
8502130	●	13.00	26.00	85.00	12.00	
8502140	●	14.00	26.00	85.00	12.00	
8502150	●	15.00	26.00	90.00	16.00	
8502160	●	16.00	32.00	100.00	16.00	

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel				
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium	Hardened Steel							
Low	Medium	High			6061	7075				Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
1010	1035	1065	4140	4340	300	400	17-4 PH		6061	7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
1018	1045								○	○							

○ Good ○ Best

