



List 8201

A BRAND AE-VML



NEW SIZES

SPEED FEED
1340-1343

CARBIDE

DUARISE

42-44°

REG


SHANK
h6

LONG

REG

PACKED
1 PIECE

Cutting Diameter Tolerance	
1/4" ≤ D ≤ 3/8"	+0 / -0.0008"
1/2" ≤ D ≤ 1"	+0 / -0.0012"



EDP Number	Flute Count	Diameter	Length of Cut	Overall Length	Shank Diameter	Number of Flutes
		D (Fractional Size)	Lc (Inch)	L (Inch)	d (Inch)	
82010021	●	1/4	0.750	2.750	0.250	4
82010121	●	1/4	1.000	2.750	0.250	4
82010221	●	5/16	0.938	3.500	0.313	4
82010321	●	5/16	1.250	3.500	0.313	4
82010421	●	3/8	1.125	3.750	0.375	4
82010521	●	3/8	1.500	4.000	0.375	4
82010621	●	1/2	1.500	4.000	0.500	4
82010721	●	1/2	2.000	4.500	0.500	4
82010821	●	5/8	1.875	5.000	0.625	5
82010921	●	5/8	2.500	5.500	0.625	5
82011021	●	3/4	2.250	5.500	0.750	5
82011121	●	3/4	3.000	6.000	0.750	5
82011221	●	1	3.000	7.000	1.000	5
82011321	●	1	4.000	7.000	1.000	5

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P Steel					M Stainless Steel			K Cast Iron	N Non-Ferrous		S HRSA		H Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High							6061	7075						
1010	1035	1065	4140	4340	300	400	17-4 PH						~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

