



A Brand AE-NIK-VML

Advanced Performance Anti-Vibration Nicked Carbide End Mills

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

List 8208

A BRAND AE-NIK-VML, Nicked



NEW SIZES

SPEED FEED
1340-1343

CARBIDE

DUARISE

42-44°



SHANK
h6

LONG

PACKED
1 PIECE



Cutting Diameter Tolerance	
6mm ≤ D ≤ 12mm	+0 / -0.020mm
16mm ≤ D ≤ 20mm	+0 / -0.030mm

EDP Number		Diameter		Length of Cut		Overall Length		Shank Diameter		Number of Flutes
		D (mm)		Lc (mm)		L (mm)		d (mm)		
8556321	●	6.00		19.00		70.00		6.00		4
8556329	●	6.00		24.00		70.00		6.00		4
8556323	●	8.00		25.00		80.00		8.00		4
8556331	●	8.00		32.00		90.00		8.00		4
8556325	●	10.00		31.00		90.00		10.00		4
8556333	●	10.00		40.00		100.00		10.00		4
8556327	●	12.00		38.00		100.00		12.00		4
8556335	●	12.00		48.00		110.00		12.00		4
8556375	●	16.00		50.00		125.00		16.00		5
8556379	●	16.00		64.00		140.00		16.00		5
8556377	●	20.00		62.00		135.00		20.00		5
8556381	●	20.00		80.00		155.00		20.00		5

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium							
Low	Medium	High			6061	7075				Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
1010	1035	1065	4140	4340	300	400	17-4 PH	6061	7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

