



A Brand AE-CR-VMFE

Advanced Performance Anti-Vibration Reduced Shank Carbide End Mills

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX


List 8246

A BRAND AE-CR-VMFE



NEW	SPEED FEED 1344	CARBIDE	DUARISE	4 FLUTE	40-44°	SHRINK FIT	REG	PACKED 1 PIECE
------------	---------------------------	----------------	----------------	----------------	---------------	-------------------	------------	--------------------------

Cutting Diameter Tolerance	
6mm ≤ D ≤ 12mm	+0 / -0.020mm



EDP Number		Diameter		Corner Radius	Length of Cut	Overall Length	Shank Diameter
		D (mm)	R (mm)	R (mm)	Lc (mm)	L (mm)	d (mm)
8549945	▲	6.00	0.50	15.00	100.00	4.00	
8549955	▲	8.00	0.50	20.00	110.00	6.00	
8549965	▲	10.00	0.50	25.00	130.00	8.00	
8549966	▲	10.00	1.00	25.00	130.00	8.00	
8549975	▲	12.00	0.50	30.00	150.00	10.00	
8549976	▲	12.00	1.00	30.00	150.00	10.00	

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked
 Note: The radius chamfering is not a full radius since it is for preventing streaks during step milling.



P					M			K	N		S		H					
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel					
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium						
Low	Medium	High			300	400	17-4 PH	6061 7075	Casting	Inconel			6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
1010	1035	1065	4140	4340	○	○	○	○	○	○	○	○	○	○	○	○	○	○
1018	1045				○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

