



List 9010

EXOCARB® MAX-BN-EBD

SPEED FEED 1488	CARBIDE	WXS	2 FLUTE	30°		SHANK h6	STUB	PACKED 1 PIECE
---------------------------	----------------	------------	----------------	------------	--	--------------------	-------------	--------------------------

Radius Tolerance	
1/32" ≤ D ≤ 1/4"	+/- 0.0002"
5/16" ≤ D ≤ 1/2"	+/- 0.0003



EDP Number		Diameter		Length of Cut	Overall Length	Shank Diameter
		D (Fractional Size)	Lc (Inch)	L (Inch)	d (Inch)	
90100111	●	1/32	0.047	2.000	0.250	
90100311	●	1/16	0.094	2.000	0.250	
90100711	●	1/8	0.188	2.000	0.250	
90100911	●	3/16	0.281	2.000	0.250	
90101111	●	1/4	0.375	2.000	0.250	
90101311	●	5/16	0.469	2.188	0.313	
90101411	●	3/8	0.563	2.188	0.375	
90101611	●	1/2	0.688	2.500	0.500	

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: Designed for faster speeds and feeds with larger depth of cut.



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium				
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1045	1065	4140				4340	7075							
○	○	○	○	○	○	○	○	○		○	○	○	○	○	○	○

○ Good ○ Best

