



List 9011

EXOCARB® MAX-BN-LS-EBD, Long Shank

SPEED FEED 1488	CARBIDE	WXS	2 FLUTE	30°		SHANK h6	STUB	PACKED 1 PIECE
---------------------------	----------------	------------	----------------	------------	--	--------------------	-------------	--------------------------

Radius Tolerance	
1/32" ≤ D ≤ 3/8"	+/- 0.0007



EDP Number		Diameter	Length of Cut	Overall Length	Shank Diameter
		D (Fractional Size)	Lc (Inch)	L (Inch)	d (Inch)
90110111	●	1/32	0.047	3.000	0.250
90110211	●	1/16	0.094	3.000	0.250
90110311	●	1/8	0.188	3.000	0.250
90110411	●	3/16	0.281	3.000	0.250
90110511	●	1/4	0.375	3.000	0.250
90110611	●	5/16	0.469	3.188	0.313
90110711	●	3/8	0.563	3.188	0.375

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked
 Note: Designed for faster speeds and feeds with larger depth of cut.



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P Steel					M Stainless Steel			K Cast Iron	N Non-Ferrous		S HRSA		H Hardened Steel											
Carbon Steel			Alloy Steel	Die Steel				Cast Iron	Aluminum		Nickel Alloy	Titanium												
Low	Medium	High			300	400	17-4 PH		6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC						
1010	1035	1065	4140																					
1018	1045		4340																					

○ Good ⊗ Best

