



List 905

OSG Carbide Bur SM-Pointed Cone

SPEED FEED 1518	CARBIDE	BR	STUB	REG	LONG	PACKED 1 PIECE
---------------------------	----------------	-----------	-------------	------------	-------------	--------------------------



EDP Number		Diameter		Length of Cut		Included Angle	Overall Length		Shank Diameter		Style
		D (Fractional Size)	D (mm)	Lc (Inch)	Lc (mm)	α (°)	L (Inch)	L (mm)	d (Inch)	d (mm)	
905-2362	●	-	6.00	-	12.70	22.00	-	50.00	-	6.00	SM-1M
905-2363	●	-	6.00	-	19.00	14.00	-	50.00	-	6.00	SM-2M
905-2364	●	-	6.00	-	25.00	10.00	-	50.00	-	6.00	SM-3M
905-2500	●	1/4	-	0.500	-	22.00	2.000	-	0.250	-	SM-1
905-2501	●	1/4	-	0.750	-	14.00	2.000	-	0.250	-	SM-2
905-2502	●	1/4	-	1.000	-	10.00	2.000	-	0.250	-	SM-3
905-3750	●	3/8	-	0.625	-	28.00	2.500	-	0.250	-	SM-4
905-3750-60	●	-	9.50	-	16.00	28.00	-	63.00	-	6.00	SM-4M
905-5000	●	1/2	-	0.875	-	28.00	2.500	-	0.250	-	SM-5
905-5000-60	●	-	12.70	-	22.00	28.00	-	69.00	-	6.00	SM-5M
905-6250	●	5/8	-	1.000	-	31.00	2.500	-	0.250	-	SM-6
905-6250-60	●	-	16.00	-	25.00	31.00	-	73.00	-	6.00	SM-6M

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: Tool diameter $\leq 1/4"$ / 6mm have brazed carbide shanks, all others have hardened steel shanks.



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

