

## List 907

OSG Carbide Bur SL-14° Included Angle

<b>SPEED FEED</b> 1518	<b>CARBIDE</b>	<b>BR</b>	<b>REG</b>	<b>PACKED</b> 1 PIECE
---------------------------	----------------	-----------	------------	--------------------------



EDP Number		Diameter		Length of Cut		Included Angle	Overall Length		Shank Diameter		Style
		D (Fractional Size)	D (mm)	Lc (Inch)	Lc (mm)	α (°)	L (Inch)	L (mm)	d (Inch)	d (mm)	
907-2362	●	-	6.00	-	16.00	14.00	-	50.00	-	6.00	SL-1M
907-2500	●	1/4	-	0.625	-	14.00	2.021	-	0.250	-	SL-1
907-3125	●	5/16	-	0.875	-	14.00	2.795	-	0.250	-	SL-2
907-3125-60	●	-	8.00	-	22.00	14.00	-	69.00	-	6.00	SL-2M
907-3750	●	3/8	-	1.063	-	14.00	3.000	-	0.250	-	SL-3
907-3750-60	●	-	9.50	-	27.00	14.00	-	74.00	-	6.00	SL-3M
907-5000	●	1/2	-	1.125	-	14.00	3.015	-	0.250	-	SL-4
907-5000-60	●	-	12.70	-	28.00	14.00	-	76.00	-	6.00	SL-4M
907-6250	●	5/8	-	1.313	-	14.00	3.187	-	0.250	-	SL-5
907-6250-60	●	-	16.00	-	30.00	14.00	-	77.00	-	6.00	SL-5M
907-7500	●	3/4	-	1.500	-	14.00	3.359	-	0.250	-	SL-7
907-7500-60	●	-	19.00	-	38.00	14.00	-	85.00	-	6.00	SL-7M

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: Tool diameter ≤ 1/4" / 6mm have brazed carbide shanks, all others have hardened steel shanks.



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

