



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

List 9140

EXOCARB® MAX HARD-EMS

SPEED FEED 1373	CARBIDE	WXS	6 FLUTE	45°		SHANK h6	REG	PACKED 1 PIECE
---------------------------	----------------	------------	----------------	------------	--	--------------------	------------	--------------------------

Cutting Diameter Tolerance	
3mm ≤ D ≤ 12mm	+0 / -0.020mm



EDP Number		Diameter		Length of Cut		Overall Length		Shank Diameter	
		D (mm)		Lc (mm)		L (mm)		d (mm)	
91400311	●	3.00		8.00		45.00		6.00	
91400411	●	4.00		11.00		45.00		6.00	
91400511	●	5.00		13.00		50.00		6.00	
91400611	●	6.00		13.00		50.00		6.00	
91400811	●	8.00		19.00		60.00		8.00	
91401011	●	10.00		22.00		70.00		10.00	
91401211	●	12.00		26.00		75.00		12.00	

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H						
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel						
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium										
Low	Medium	High			6061	Casting				Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC				
1010	1035	1065	4140	4340	300	400	17-4 PH		6061	7075									
○	○	○	○	○	○	○	○	○			○	○	○	○	○	○	○	○	○

○ Good ○ Best

