



List 9144

EXOCARB® MAX HARD-EMS

SPEED FEED 1373	CARBIDE	WXS	6 FLUTE	45°		SHANK h6	REG	PACKED 1 PIECE
--------------------	---------	-----	---------	-----	--	-------------	-----	-------------------

Cutting Diameter Tolerance	
6mm ≤ D ≤ 12mm	+0 / -0.020mm



EDP Number	Diameter	Corner Radius	Length of Cut	Overall Length	Shank Diameter
91440611	6.00	0.50	13.00	50.00	6.00
91440811	8.00	0.50	19.00	60.00	8.00
91441011	10.00	0.50	22.00	70.00	10.00
91441111	10.00	1.00	22.00	70.00	10.00
91441211	12.00	0.50	26.00	75.00	12.00
91441311	12.00	1.00	26.00	75.00	12.00

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium	Hardened Steel						
Low	Medium	High			6061	Casting				6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC		
1010	1035	1065	4140	4340	300	400	17-4 PH	6061	7075	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	

○ Good ○ Best

