



List 9191

EXOCARB® MAX CBN-SXB

SPEED FEED 1489	CBN	BR	2 FLUTE	30°		SHANK h6	STUB	PACKED 1 PIECE
---------------------------	------------	-----------	----------------	------------	--	--------------------	-------------	--------------------------

Radius Tolerance	
0.4mm ≤ D ≤ 3mm	+/- 0.005mm



EDP Number	Diameter	Length of Cut	Neck Length	Overall Length	Shank Diameter	
						D (mm)
8525304	●	0.40	0.30	1.20	45.00	4.00
8525305	●	0.50	0.30	1.50	45.00	4.00
8525306	●	0.60	0.40	1.80	45.00	4.00
8525307	●	0.70	0.50	2.10	45.00	4.00
8525308	●	0.80	0.50	2.40	45.00	4.00
8525309	●	0.90	0.60	2.70	45.00	4.00
8525310	●	1.00	0.60	2.50	45.00	4.00
8525210	●	1.00	0.60	2.50	50.00	6.00
8525211	●	1.10	0.70	2.80	50.00	6.00
8525212	●	1.20	0.70	3.00	50.00	6.00
8525213	●	1.30	0.80	3.30	50.00	6.00
8525214	●	1.40	0.80	3.50	50.00	6.00
8525215	●	1.50	0.90	3.80	50.00	6.00
8525216	●	1.60	1.00	4.00	50.00	6.00
8525217	●	1.70	1.00	4.30	50.00	6.00
8525218	●	1.80	1.10	4.50	50.00	6.00
8525219	●	1.90	1.10	4.80	50.00	6.00
8525220	●	2.00	1.20	5.00	50.00	6.00
8525221	●	2.10	1.30	4.20	50.00	6.00
8525222	●	2.20	1.30	4.40	50.00	6.00
8525223	●	2.30	1.40	4.60	50.00	6.00
8525224	●	2.40	1.40	4.80	50.00	6.00
8525225	●	2.50	1.50	5.00	50.00	6.00
8525226	●	2.60	1.60	5.20	50.00	6.00
8525227	●	2.70	1.60	5.40	50.00	6.00
8525228	●	2.80	1.70	5.60	50.00	6.00
8525229	●	2.90	1.70	5.80	50.00	6.00
8525230	●	3.00	1.80	6.00	50.00	6.00

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium				
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340									○	⊙	⊙	
1018	1045															

○ Good ⊙ Best

