



List 952

OSG Carbide Bur SN-Inverted Taper

SPEED FEED 1518	CARBIDE	BR	STUB	PACKED 1 PIECE
--------------------	---------	----	------	-------------------



EDP Number		Diameter		Length of Cut		Included Angle	Overall Length		Shank Diameter		Style
		D (Fractional Size)	D (mm)	Lc (Inch)	Lc (mm)	α (°)	L (Inch)	L (mm)	d (Inch)	d (mm)	
952-2362	●	-	6.00	-	8.00	10.00	-	50.00	-	6.00	SN-1M
952-2500	●	1/4	-	0.313	-	10.00	2.000	-	0.250	-	SN-1
952-3750	●	3/8	-	0.375	-	13.00	2.125	-	0.250	-	SN-2
952-3750-60	●	-	9.50	-	9.50	13.00	-	53.00	-	6.00	SN-2M
952-5000	●	1/2	-	0.500	-	28.00	2.250	-	0.250	-	SN-4
952-5000-60	●	-	12.70	-	12.70	28.00	-	57.00	-	6.00	SN-4M
952-6250	●	5/8	-	0.750	-	18.00	2.500	-	0.250	-	SN-6
952-6250-60	●	-	16.00	-	19.00	18.00	-	63.00	-	6.00	SN-6M
952-7500	●	3/4	-	0.625	-	30.00	2.375	-	0.250	-	SN-7
952-7500-60	●	-	19.00	-	16.00	30.00	-	60.00	-	6.00	SN-7M

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: Tool diameter \leq 1/4" / 6mm have brazed carbide shanks, all others have hardened steel shanks.