




List 11052

EXOTAP® DC VP-DC-HT, DIN Overall Length



EDP		Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes
				L (mm)	Lc (mm)	L1 (mm)	d (mm)	k (mm)	lk (mm)	
1105200108	●	M6 x 1	D5	80.00	12.00	30.00	6.48	4.85	7.94	3
1105200208	●	M8 x 1.25	D5	90.00	15.00	35.00	8.08	6.05	9.53	4
1105200308	●	M10 x 1	D5	90.00	18.00	39.00	9.68	7.26	11.11	4
1105200408	●	M10 x 1.25	D6	100.00	18.00	39.00	9.68	7.26	11.11	4
1105200508	●	M10 x 1.5	D6	100.00	18.00	39.00	9.68	7.26	11.11	4
1105200608	●	M12 x 1.25	D6	100.00	21.00	49.10	9.32	6.99	11.11	4
1105200708	●	M12 x 1.5	D6	100.00	21.00	49.10	9.32	6.99	11.11	4
1105200808	●	M12 x 1.75	D6	110.00	21.00	49.10	9.32	6.99	11.11	4
1105200908	●	M14 x 1.5	D7	100.00	24.00	50.10	10.90	8.18	12.70	5
1105201008	●	M14 x 2	D7	110.00	24.00	50.10	10.90	8.18	12.70	5
1105201108	●	M16 x 1.5	D6	100.00	24.00	54.00	12.19	9.14	14.29	5
1105201208	●	M16 x 2	D7	110.00	24.00	54.00	12.19	9.14	14.29	5
1105201308	●	M18 x 1.5	D6	110.00	30.00	55.00	13.77	10.31	15.88	5
1105201408	●	M18 x 2	D7	125.00	30.00	55.00	13.77	10.31	15.88	5
1105201508	●	M18 x 2.5	D7	125.00	30.00	55.00	13.77	10.31	15.88	5
1105201608	●	M20 x 1.5	D6	125.00	30.00	61.80	16.56	12.42	17.46	5
1105201708	●	M20 x 2	D7	140.00	30.00	61.80	16.56	12.42	17.46	5
1105201808	●	M20 x 2.5	D7	140.00	30.00	61.80	16.56	12.42	17.46	5
1105201908	●	M22 x 1.5	D6	125.00	30.00	67.40	17.70	13.28	19.05	5
1105202008	●	M22 x 2	D8	140.00	30.00	67.40	17.70	13.28	19.05	5
1105202108	●	M22 x 2.5	D8	140.00	30.00	67.40	17.70	13.28	19.05	5
1105202208	●	M24 x 1.5	D6	140.00	36.00	68.40	19.30	14.48	19.05	5
1105202308	●	M24 x 2	D8	140.00	36.00	68.40	19.30	14.48	19.05	5
1105202408	●	M24 x 3	D8	160.00	36.00	68.40	19.30	14.48	19.05	5

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel				
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium					
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC
1010	1035	1065	4140	4340	300	400	17-4 PH	25-75 SFM	6061	7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
1018	1045								40-65 SFM								

○ Good ○ Best

