



List 2110

EXOCARB® AERO UVX-TI-LN-CR-5FL, Reduced Neck

SPEED FEED 1375	CARBIDE	EXO	5 FLUTE	41-43°		SHANK h6	REG	PACKED 1 PIECE
---------------------------	----------------	------------	----------------	---------------	--	--------------------	------------	--------------------------

Cutting Diameter Tolerance	
12mm ≤ D ≤ 20mm	+0 / -0.050mm



EDP Number		Diameter		Corner Radius	Length of Cut		Neck Length	Neck Diameter	Overall Length	Shank Diameter
		D (mm)	R (mm)	R (mm)	Lc (mm)	L1 (mm)	d1 (mm)	L (mm)	d (mm)	
8555321	●	12.00	1.00	1.00	24.00	36.00	11.50	90.00	12.00	
8555322	●	12.00	1.50	1.50	24.00	36.00	11.50	90.00	12.00	
8555323	●	12.00	2.00	2.00	24.00	36.00	11.50	90.00	12.00	
8555324	●	12.00	2.50	2.50	24.00	36.00	11.50	90.00	12.00	
8555325	●	12.00	3.00	3.00	24.00	36.00	11.50	90.00	12.00	
8555326	●	12.00	4.00	4.00	24.00	36.00	11.50	90.00	12.00	
8555361	●	16.00	1.00	1.00	32.00	48.00	15.50	100.00	16.00	
8555362	●	16.00	1.50	1.50	32.00	48.00	15.50	100.00	16.00	
8555363	●	16.00	2.00	2.00	32.00	48.00	15.50	100.00	16.00	
8555364	●	16.00	2.50	2.50	32.00	48.00	15.50	100.00	16.00	
8555365	●	16.00	3.00	3.00	32.00	48.00	15.50	100.00	16.00	
8555366	●	16.00	4.00	4.00	32.00	48.00	15.50	100.00	16.00	
8555401	●	20.00	1.00	1.00	40.00	60.00	19.50	120.00	20.00	
8555402	●	20.00	1.50	1.50	40.00	60.00	19.50	120.00	20.00	
8555403	●	20.00	2.00	2.00	40.00	60.00	19.50	120.00	20.00	
8555404	●	20.00	2.50	2.50	40.00	60.00	19.50	120.00	20.00	
8555405	●	20.00	3.00	3.00	40.00	60.00	19.50	120.00	20.00	
8555406	●	20.00	4.00	4.00	40.00	60.00	19.50	120.00	20.00	
8555407	●	20.00	5.00	5.00	40.00	60.00	19.50	120.00	20.00	

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H					
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel					
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium						
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
1010	1035	1065	4140	4340	300	400	17-4 PH		6061	7075								
1018	1045				○	○	○					◎						

○ Good ◎ Best

