



List 2953

EXOCARB® AERO-ETXL

SPEED FEED 1378	CARBIDE	DLC	3 FLUTE	35°				SHANK h6	EXTRA LONG	PACKED 1 PIECE
---------------------------	----------------	------------	----------------	------------	--	--	--	--------------------	-------------------	--------------------------

Cutting Diameter Tolerance	
D = 20mm	+0 / -0.020mm



EDP Number		Diameter		Corner Radius	Length of Cut	Overall Length	Shank Diameter
		D (mm)	R (mm)	R (mm)	Lc (mm)	L (mm)	d (mm)
8533400	●	20.00	-		100.00	160.00	20.00
8533401	●	20.00	1.00		100.00	160.00	20.00
8533402	●	20.00	1.60		100.00	160.00	20.00
8533403	●	20.00	3.00		100.00	160.00	20.00
8533404	●	20.00	4.00		100.00	160.00	20.00
8533405	●	20.00	5.00		100.00	160.00	20.00

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H					
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel					
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium						
Low	Medium	High			300	400	17-4 PH		6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
1010	1035	1065	4140	4340														
1018	1045								○	○								

○ Good ○ Best

