



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

## List 3642

EXOCARB® WXL®-EML



SPEED FEED  
1372

CARBIDE

WXL



30°



SHANK  
h6

LONG

EXTRA LONG

PACKED  
1 PIECE

Cutting Diameter Tolerance	
1/16" ≤ D ≤ 1/2"	+0 / -0.0008"
5/8" ≤ D	+0 / -0.0012"



EDP Number	Diameter	Length of Cut	Overall Length	Shank Diameter	
					D (Fractional Size)
36420012	●	1/16	0.250	1.500	0.125
36420112	○	5/64	0.313	1.500	0.125
36420212	●	3/32	0.500	1.500	0.125
36420312	○	7/64	0.500	1.500	0.125
36420412	●	1/8	0.625	1.500	0.125
36420512	●	5/32	0.688	2.000	0.188
36420612	●	3/16	0.750	2.000	0.188
36420712	●	7/32	0.875	2.500	0.250
36420812	●	1/4	1.000	2.500	0.250
36420912	●	5/16	1.125	3.000	0.313
36421012	●	3/8	1.375	4.000	0.375
36421112	●	1/2	1.625	4.000	0.500
36421212	●	5/8	2.000	5.000	0.625

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High			300	400	17-4 PH		6061 7075	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

