



List 4571

EXOCARB® WXS-PKE, Reduced Neck



SPEED FEED
1441

CARBIDE

WXS




SHANK
h6

STUB

PACKED
1 PIECE

Cutting Diameter Tolerance	
3mm ≤ D ≤ 12mm	+0 / -0.020mm



EDP Number		Diameter		Corner Radius	Length of Cut	Neck Length	Neck Diameter	Overall Length	Shank Diameter
		D (mm)	R (mm)	R (mm)	Lc (mm)	L1 (mm)	d1 (mm)	L (mm)	d (mm)
457103011	●	3.00	0.20	0.20	5.00	9.00	2.85	60.00	6.00
457103111	●	3.00	0.20	0.20	5.00	15.00	2.85	70.00	6.00
457103211	●	3.00	0.50	0.50	5.00	9.00	2.85	60.00	6.00
457103311	●	3.00	0.50	0.50	5.00	15.00	2.85	70.00	6.00
457104011	●	4.00	0.20	0.20	6.00	12.00	3.80	70.00	6.00
457104111	●	4.00	0.20	0.20	6.00	20.00	3.80	80.00	6.00
457104211	●	4.00	0.50	0.50	6.00	12.00	3.80	70.00	6.00
457104311	●	4.00	0.50	0.50	6.00	20.00	3.80	80.00	6.00
457105011	●	5.00	0.20	0.20	8.00	15.00	4.80	80.00	6.00
457105111	●	5.00	0.20	0.20	8.00	25.00	4.80	90.00	6.00
457105211	●	5.00	0.50	0.50	8.00	15.00	4.80	80.00	6.00
457105311	●	5.00	0.50	0.50	8.00	25.00	4.80	90.00	6.00
457106011	●	6.00	0.50	0.50	9.00	18.00	5.80	90.00	6.00
457106311	●	6.00	0.50	0.50	9.00	30.00	5.80	100.00	6.00
457106111	●	6.00	1.00	1.00	9.00	18.00	5.80	90.00	6.00
457106211	●	6.00	1.00	1.00	9.00	30.00	5.80	100.00	6.00
457108011	●	8.00	0.50	0.50	12.00	24.00	7.70	100.00	8.00
457108111	●	8.00	0.50	0.50	12.00	40.00	7.70	110.00	8.00
457108211	●	8.00	1.00	1.00	12.00	24.00	7.70	100.00	8.00
457108311	●	8.00	1.00	1.00	12.00	40.00	7.70	110.00	8.00
457110011	●	10.00	0.50	0.50	15.00	30.00	9.70	100.00	10.00
457110111	●	10.00	0.50	0.50	15.00	50.00	9.70	120.00	10.00
457110211	●	10.00	1.00	1.00	15.00	30.00	9.70	100.00	10.00
457110311	●	10.00	1.00	1.00	15.00	50.00	9.70	120.00	10.00
457110411	●	10.00	2.00	2.00	15.00	30.00	9.70	100.00	10.00
457110511	●	10.00	2.00	2.00	15.00	50.00	9.70	120.00	10.00
457112011	●	12.00	1.00	1.00	18.00	36.00	11.70	110.00	12.00
457112111	●	12.00	1.00	1.00	18.00	60.00	11.70	130.00	12.00
457112211	●	12.00	2.00	2.00	18.00	36.00	11.70	110.00	12.00
457112311	●	12.00	2.00	2.00	18.00	60.00	11.70	130.00	12.00

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H						
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel						
Carbon Steel			Alloy Steel	Die Steel					Aluminum	Nickel Alloy	Titanium								
Low	Medium	High							6061 7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC			
1010	1035	1065	4140	4340	300	400	17-4 PH												
○	○	○	○	○	○	○	○	○			○	○	○	○	○	○	○	○	○

○ Good ○ Best

