




List 496

OSG STANDARD CARBIDE CR

SPEED FEED 1402-1405	CARBIDE	4 FLUTE	30°		STUB	REG	LONG	PACKED 1 PIECE
--------------------------------	----------------	----------------	------------	--	-------------	------------	-------------	--------------------------

Cutting Diameter Tolerance	
1/8" ≤ D ≤ 1"	+0 / -0.002"



EDP Number	Diameter	Corner Radius	Length of Cut	Overall Length	Shank Diameter	Surface Treatment
496-1251	1/8	0.015	0.500	1.500	0.125	BRIGHT
496-125111	1/8	0.015	0.500	1.500	0.125	TiAIN
496-1872	3/16	0.020	0.625	2.000	0.188	BRIGHT
496-187211	3/16	0.020	0.625	2.000	0.188	TiAIN
496-1873	3/16	0.030	0.625	2.000	0.188	BRIGHT
496-187311	3/16	0.030	0.625	2.000	0.188	TiAIN
496-2502	1/4	0.020	0.750	2.500	0.250	BRIGHT
496-250211	1/4	0.020	0.750	2.500	0.250	TiAIN
496-2503	1/4	0.030	0.750	2.500	0.250	BRIGHT
496-250311	1/4	0.030	0.750	2.500	0.250	TiAIN
496-2504	1/4	0.045	0.750	2.500	0.250	BRIGHT
496-3122	5/16	0.020	0.813	2.500	0.313	BRIGHT
496-312211	5/16	0.020	0.813	2.500	0.313	TiAIN
496-3123	5/16	0.030	0.813	2.500	0.313	BRIGHT
496-312311	5/16	0.030	0.813	2.500	0.313	TiAIN
496-3124	5/16	0.045	0.813	2.500	0.313	BRIGHT
496-3752	3/8	0.020	1.000	2.500	0.375	BRIGHT
496-375211	3/8	0.030	1.000	2.500	0.375	BRIGHT
496-375311	3/8	0.030	1.000	2.500	0.375	TiAIN
496-3754	3/8	0.045	1.000	2.500	0.375	BRIGHT
496-375411	3/8	0.045	1.000	2.500	0.375	TiAIN
496-5002	1/2	0.020	1.000	3.000	0.500	BRIGHT
496-500211	1/2	0.020	1.000	3.000	0.500	TiAIN
496-5003	1/2	0.030	1.000	3.000	0.500	BRIGHT
496-500311	1/2	0.030	1.000	3.000	0.500	TiAIN
496-5004	1/2	0.045	1.000	3.000	0.500	BRIGHT
496-5006	1/2	0.060	1.000	3.000	0.500	BRIGHT
496-500611	1/2	0.060	1.000	3.000	0.500	TiAIN
496-6252	5/8	0.020	1.250	3.500	0.625	BRIGHT
496-6253	5/8	0.030	1.250	3.500	0.625	BRIGHT
496-6254	5/8	0.045	1.250	3.500	0.625	BRIGHT
496-6256	5/8	0.060	1.250	3.500	0.625	BRIGHT
496-6259	5/8	0.090	1.250	3.500	0.625	BRIGHT
496-7502	3/4	0.020	1.500	4.000	0.750	BRIGHT
496-7503	3/4	0.030	1.500	4.000	0.750	BRIGHT
496-750311	3/4	0.030	1.500	4.000	0.750	TiAIN
496-7504	3/4	0.045	1.500	4.000	0.750	BRIGHT
496-7506	3/4	0.060	1.500	4.000	0.750	BRIGHT
496-7509	3/4	0.090	1.500	4.000	0.750	BRIGHT
496-7500	3/4	0.125	1.500	4.000	0.750	BRIGHT
496-1002	1	0.020	1.500	4.000	1.000	BRIGHT
496-1003	1	0.030	1.500	4.000	1.000	BRIGHT
496-1004	1	0.045	1.500	4.000	1.000	BRIGHT
496-1006	1	0.060	1.500	4.000	1.000	BRIGHT
496-1009	1	0.090	1.500	4.000	1.000	BRIGHT
496-1000	1	0.125	1.500	4.000	1.000	BRIGHT

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: Other coatings available upon request.



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium				
Low	Medium	High							6061	Casting			Inconel	6Al4V	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340				7075				(30 HRC)				
○	○	○	○	○	○	○	○	○	○	○			○	○	○	○

○ Good ⊗ Best

