



# EXOCARB® DG-CR-EML

Long Length of Cut DG Coated 4-Fluted Corner Radius End Mills for Graphite

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

## List 7470

EXOCARB® DG-CR-EML

<b>NEW</b>	<b>SPEED FEED</b> 1455	<b>CARBIDE</b>	<b>DG</b>	<b>4 FLUTE</b>	<b>30°</b>		<b>SHANK</b> h4	<b>LONG</b>	<b>PACKED</b> 1 PIECE
------------	---------------------------	----------------	-----------	----------------	------------	--	--------------------	-------------	--------------------------



Cutting Diameter Tolerance	
3/64" ≤ D ≤ 3/16"	+/- 0.00028"
1/4" ≤ D ≤ 1/2"	+/- 0.00039"

EDP Number		Diameter		Corner Radius	Length of Cut	Overall Length	Shank Diameter
		D (Fractional Size)	R (Inch)	Lc (Inch)	L (Inch)	d (Inch)	
74700125	○	3/64	0.010	0.234	2.500	0.125	
74700225	○	1/16	0.010	0.313	2.500	0.125	
74700325	○	3/32	0.015	0.469	2.500	0.125	
74700425	○	3/32	0.020	0.469	2.500	0.125	
74700525	○	1/8	0.015	0.625	3.000	0.125	
74700625	○	1/8	0.020	0.625	3.000	0.125	
74700725	○	1/8	0.030	0.625	3.000	0.125	
74700825	○	3/16	0.030	0.938	3.000	0.188	
74700925	○	3/16	0.060	0.938	3.000	0.188	
74701025	○	1/4	0.015	1.250	4.000	0.250	
74701125	○	1/4	0.020	1.250	4.000	0.250	
74701225	○	1/4	0.030	1.250	4.000	0.250	
74701325	○	1/4	0.060	1.250	4.000	0.250	
74701425	○	3/8	0.015	1.875	6.000	0.375	
74701525	○	3/8	0.030	1.875	6.000	0.375	
74701625	○	3/8	0.060	1.875	6.000	0.375	
74701725	○	1/2	0.015	2.250	6.000	0.500	
74701825	○	1/2	0.030	2.250	6.000	0.500	
74701925	○	1/2	0.060	2.250	6.000	0.500	

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N			S		Other		
Steel					Stainless Steel			Cast Iron	Non-Ferrous			HRSA		Graphite	Cobalt-Chrome	
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Mg		Brass, Bronze	Nickel Alloy	Titanium					
Low	Medium	High			6061	Casting						Inconel	6Al4V (30 HRC)			
1010	1035	1065	4140	4340	300	400	17-4 PH	6061	7075							

○ Good ○ Best

