



List 8210

A BRAND AE-CR-VMS



SPEED FEED
1425-1426

CARBIDE

DUARISE

4 FLUTE

37-40°




SHRINK FIT

STUB

REG

PACKED
1 PIECE



Cutting Diameter Tolerance	
3/16" ≤ D ≤ 7/16"	+0 / -0.0008"
1/2" ≤ D ≤ 1"	+0 / -0.0012"

Radius Tolerance	
0.015 ≤ R ≤ 0.125	+/- 0.0008"

EDP Number	Dia.	Corner Radius	Length of Cut	Overall Length	Shank Dia.
		R (inch)	Lc (inch)	L (inch)	d (inch)
82100021	3/16	0.015	0.438	2.000	0.188
82100221	3/16	0.030	0.438	2.000	0.188
82100421	1/4	0.015	0.438	2.500	0.250
82100621	1/4	0.030	0.438	2.500	0.250
82100821	5/16	0.015	0.813	2.500	0.313
82101021	5/16	0.030	0.813	2.500	0.313
82101221	3/8	0.015	0.500	2.500	0.375
82101421	3/8	0.030	0.500	2.500	0.375
82101621	3/8	0.045	0.500	2.500	0.375
82101821	3/8	0.060	0.500	2.500	0.375
82102021	3/8	0.015	0.875	2.500	0.375
82102221	3/8	0.030	0.875	2.500	0.375
82102421	3/8	0.045	0.875	2.500	0.375
82102621	3/8	0.060	0.875	2.500	0.375
82102821	7/16	0.015	1.000	2.750	0.438
82103021	7/16	0.030	1.000	2.750	0.438
82103221	1/2	0.015	0.625	2.500	0.500
82103421	1/2	0.030	0.625	2.500	0.500
82103621	1/2	0.045	0.625	2.500	0.500
82103821	1/2	0.060	0.625	2.500	0.500
82104021	1/2	0.090	0.625	2.500	0.500
82104221	1/2	0.015	1.000	3.000	0.500
82104421	1/2	0.030	1.000	3.000	0.500
82104621	1/2	0.045	1.000	3.000	0.500
82104821	1/2	0.060	1.000	3.000	0.500
82105021	1/2	0.090	1.000	3.000	0.500

EDP Number	Dia.	Corner Radius	Length of Cut	Overall Length	Shank Dia.
		R (inch)	Lc (inch)	L (inch)	d (inch)
82105221	1/2	0.015	1.250	3.500	0.500
82105421	1/2	0.030	1.250	3.500	0.500
82105621	1/2	0.045	1.250	3.500	0.500
82105821	1/2	0.060	1.250	3.500	0.500
82106021	1/2	0.090	1.250	3.500	0.500
82106221	5/8	0.030	0.750	3.000	0.625
82106421	5/8	0.060	0.750	3.000	0.625
82106621	5/8	0.090	0.750	3.000	0.625
82106821	5/8	0.125	0.750	3.000	0.625
82107021	5/8	0.030	1.250	3.500	0.625
82107221	5/8	0.060	1.250	3.500	0.625
82107421	5/8	0.090	1.250	3.500	0.625
82107621	5/8	0.125	1.250	3.500	0.625
82107821	3/4	0.030	0.875	3.500	0.750
82108021	3/4	0.060	0.875	3.500	0.750
82108221	3/4	0.090	0.875	3.500	0.750
82108421	3/4	0.125	0.875	3.500	0.750
82108621	3/4	0.030	1.500	4.000	0.750
82108821	3/4	0.060	1.500	4.000	0.750
82109021	3/4	0.090	1.500	4.000	0.750
82109221	3/4	0.125	1.500	4.000	0.750
82109421	1	0.030	1.500	4.000	1.000
82109621	1	0.060	1.500	4.000	1.000
82109821	1	0.090	1.500	4.000	1.000
82109921	1	0.125	1.500	4.000	1.000

● Stocked ○ Available Upon Request; MOQ May Apply
▲ Globally Stocked

● Stocked ○ Available Upon Request; MOQ May Apply
▲ Globally Stocked



P					M			K	N		S		H										
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel										
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium	Hardened Steel										
Low	Medium	High						6061	7075	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC					
1010	1035	1045	1065	4140	4340	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

