



## List 3794: 4 Flute, Long Neck, Stub Length

### Slotting

Hardness		-			<32 HRC			33-41 HRC			42-50 HRC		
Work Material		Copper Copper Alloy			Mild Steels Carbon Steels			Hardened Steels Pre-hardened Steels Stainless Steels					
Cutting Speed		173-374 SFM			144-309 SFM			130-309 SFM			101-248 SFM		
Depth of Cut													
D (mm)	L2 (mm)	Speed (RPM)	Feed (in/min)	aa (in)	Speed (RPM)	Feed (in/min)	aa (in)	Speed (RPM)	Feed (in/min)	aa (in)	Speed (RPM)	Feed (in/min)	aa (in)
1.0	4	25,000	62.8	0.0031	21,980	54.8	0.0028	21,300	46.1	0.0028	16,930	29.7	0.0020
	6	25,000	57.5	0.0031	21,980	51.3	0.0028	21,300	43.5	0.0024	16,930	30.0	0.0016
	8	25,000	51.9	0.0020	21,980	45.1	0.0016	21,300	40.0	0.0016	16,930	22.2	0.0012
	10	25,000	47.1	0.0016	21,980	42.8	0.0012	21,300	34.9	0.0011	16,930	20.0	0.0008
	12	25,000	47.1	0.0008	21,980	42.8	0.0008	21,300	34.9	0.0007	16,930	20.0	0.0004
1.2	16	25,000	26.3	0.0004	21,980	23.1	0.0003	21,300	25.2	0.0003	16,930	16.7	0.0002
	6	22,110	60.2	0.0039	18,310	50.2	0.0031	17,750	42.9	0.0028	14,110	29.4	0.0020
	8	22,110	52.6	0.0031	18,310	43.3	0.0028	17,750	38.6	0.0020	14,110	23.8	0.0016
	10	22,110	39.9	0.0024	18,310	33.9	0.0020	17,750	38.6	0.0016	14,110	23.8	0.0012
	12	22,110	46.7	0.0020	18,310	39.9	0.0016	17,750	32.8	0.0012	14,110	22.7	0.0008
1.4	16	22,110	36.0	0.0004	18,310	30.0	0.0003	17,750	23.5	0.0003	14,110	18.3	0.0002
	6	18,960	60.6	0.0055	15,700	49.4	0.0047	15,210	42.6	0.0043	12,090	28.6	0.0035
	8	18,960	50.3	0.0043	15,700	41.2	0.0035	15,210	37.0	0.0031	12,090	22.0	0.0024
	10	18,960	50.3	0.0028	15,700	41.2	0.0024	15,210	37.0	0.0020	12,090	22.0	0.0016
	12	18,960	50.3	0.0024	15,700	41.2	0.0020	15,210	37.0	0.0016	12,090	22.0	0.0012
	14	18,960	45.6	0.0020	15,700	38.7	0.0016	15,210	32.1	0.0014	12,090	19.5	0.0012
	16	18,960	45.6	0.0016	15,700	38.7	0.0012	15,210	32.1	0.0008	12,090	19.5	0.0008
1.5	22	18,960	31.7	0.0004	15,700	26.6	0.0002	15,210	20.6	0.0002	12,090	16.1	0.0002
	6	17,690	66.4	0.0055	14,650	54.5	0.0047	14,200	41.9	0.0043	11,290	28.6	0.0035
	8	17,690	53.2	0.0047	14,650	43.3	0.0039	14,200	39.1	0.0031	11,290	22.2	0.0028
	10	17,690	53.2	0.0039	14,650	43.3	0.0031	14,200	39.1	0.0028	11,290	22.2	0.0020
	12	17,690	53.2	0.0028	14,650	43.3	0.0024	14,200	39.1	0.0020	11,290	22.2	0.0016
	14	17,690	53.2	0.0024	14,650	43.3	0.0020	14,200	39.1	0.0018	11,290	22.2	0.0014
	16	17,690	45.1	0.0024	14,650	38.7	0.0020	14,200	32.2	0.0016	11,290	20.0	0.0012
	18	17,690	45.1	0.0016	14,650	38.7	0.0012	14,200	32.2	0.0008	11,290	20.0	0.0008
1.6	20	17,690	38.4	0.0008	14,650	32.2	0.0008	14,200	29.0	0.0006	11,290	20.0	0.0004
	6	16,590	65.3	0.0067	13,740	54.1	0.0055	13,310	41.6	0.0051	10,580	28.8	0.0039
	8	16,590	56.2	0.0063	13,740	46.9	0.0051	13,310	36.7	0.0047	10,580	22.7	0.0039
	10	16,590	52.6	0.0051	13,740	43.3	0.0043	13,310	36.7	0.0035	10,580	22.7	0.0028
	12	16,590	52.6	0.0031	13,740	43.3	0.0028	13,310	36.7	0.0024	10,580	22.7	0.0020
	14	16,590	52.6	0.0028	13,740	43.3	0.0024	13,310	36.7	0.0020	10,580	22.7	0.0016
	16	16,590	46.3	0.0024	13,740	39.1	0.0020	13,310	30.2	0.0016	10,580	20.8	0.0014
	18	16,590	46.3	0.0020	13,740	39.1	0.0016	13,310	30.2	0.0012	10,580	20.8	0.0012
1.8	20	16,590	46.3	0.0008	13,740	39.1	0.0008	13,310	30.2	0.0008	10,580	20.8	0.0004
	25	16,590	34.2	0.0004	13,740	27.9	0.0004	13,310	21.2	0.0004	10,580	15.0	0.0003
	6	14,740	68.7	0.0094	12,210	57.1	0.0079	11,830	46.6	0.0071	9,410	32.4	0.0055
	8	14,740	77.9	0.0091	12,210	57.1	0.0075	11,830	46.6	0.0067	9,410	32.4	0.0051
	10	14,740	49.5	0.0055	12,210	41.2	0.0047	11,830	34.9	0.0039	9,410	27.8	0.0031
	12	14,740	49.5	0.0047	12,210	41.2	0.0039	11,830	34.9	0.0031	9,410	27.8	0.0028
	14	14,740	49.5	0.0039	12,210	41.2	0.0031	11,830	34.9	0.0024	9,410	27.8	0.0020
	16	14,740	49.5	0.0031	12,210	41.2	0.0028	11,830	34.9	0.0020	9,410	27.8	0.0016
1.8	18	14,740	44.0	0.0024	12,210	37.7	0.0020	11,830	29.1	0.0018	9,410	27.8	0.0014
	20	14,740	44.0	0.0020	12,210	37.7	0.0016	11,830	29.1	0.0016	9,410	27.8	0.0012
	25	14,740	34.5	0.0004	12,210	28.8	0.0004	11,830	24.6	0.0003	9,410	18.5	0.0003

1. Use a rigid and precise machine and holder.
2. When chattering occurs, reduce the speed and feed simultaneously.
3. Use a suitable cutting fluid with high smoke retardant.
4. When length of the tool extension from the machine is long, reduce the speed and feed.





## Slotting

Hardness		-			<32 HRC			33-41 HRC			42-50 HRC		
Work Material		Copper Copper Alloy			Mild Steels Carbon Steels			Hardened Steels Pre-hardened Steels Stainless Steels					
Cutting Speed		173-374 SFM			144-309 SFM			130-309 SFM			101-248 SFM		
Depth of Cut													
D (mm)	L2 (mm)	Speed (RPM)	Feed (in/min)	aa (in)	Speed (RPM)	Feed (in/min)	aa (in)	Speed (RPM)	Feed (in/min)	aa (in)	Speed (RPM)	Feed (in/min)	aa (in)
2.0	6	13,270	68.2	0.0134	10,990	54.8	0.0110	10,650	44.9	0.0102	8,470	31.8	0.0083
	8	13,270	68.2	0.0122	10,990	54.8	0.0102	10,650	44.9	0.0087	8,470	31.8	0.0071
	10	13,270	54.3	0.0114	10,990	43.3	0.0094	10,650	36.7	0.0079	8,470	27.8	0.0063
	12	13,270	50.6	0.0063	10,990	39.9	0.0051	10,650	36.7	0.0043	8,470	27.8	0.0035
	14	13,270	50.6	0.0051	10,990	39.9	0.0043	10,650	36.7	0.0035	8,470	27.8	0.0028
	16	13,270	50.6	0.0039	10,990	39.9	0.0031	10,650	36.7	0.0028	8,470	27.8	0.0024
	18	13,270	50.6	0.0031	10,990	39.9	0.0028	10,650	36.7	0.0024	8,470	27.8	0.0020
	20	13,270	46.2	0.0024	10,990	37.0	0.0020	10,650	31.4	0.0020	8,470	28.6	0.0016
	25	13,270	46.2	0.0016	10,990	37.0	0.0012	10,650	31.4	0.0008	8,470	28.6	0.0008
30	13,270	46.2	0.0008	10,990	37.0	0.0008	10,650	31.4	0.0004	8,470	28.6	0.0004	
2.5	8	10,610	67.7	0.0165	8,790	54.8	0.0138	8,520	45.7	0.0130	6,770	31.1	0.0102
	12	10,610	67.7	0.0110	8,790	54.8	0.0091	8,520	45.7	0.0075	6,770	31.1	0.0059
	16	10,610	52.2	0.0055	8,790	41.5	0.0047	8,520	39.1	0.0039	6,770	28.6	0.0031
	20	10,610	52.2	0.0043	8,790	41.5	0.0035	8,520	39.1	0.0031	6,770	28.6	0.0024
	25	10,610	50.1	0.0039	8,790	40.7	0.0031	8,520	31.4	0.0024	6,770	26.7	0.0020
3.0	8	8,850	68.2	0.0150	7,330	54.8	0.0126	7,100	41.9	0.0118	5,640	29.2	0.0094
	12	8,850	62.4	0.0126	7,330	50.5	0.0106	7,100	41.9	0.0091	5,640	29.2	0.0071
	16	8,850	43.5	0.0094	7,330	34.6	0.0079	7,100	32.6	0.0067	5,640	27.8	0.0051
	20	8,850	43.5	0.0063	7,330	34.6	0.0051	7,100	32.6	0.0043	5,640	27.8	0.0031
	25	8,850	43.5	0.0051	7,330	34.6	0.0043	7,100	32.6	0.0035	5,640	27.8	0.0028
	30	8,850	41.7	0.0043	7,330	33.9	0.0035	7,100	29.9	0.0031	5,640	26.7	0.0024

1. Use a rigid and precise machine and holder.
2. When chattering occurs, reduce the speed and feed simultaneously.
3. Use a suitable cutting fluid with high smoke retardant.
4. When length of the tool extension from the machine is long, reduce the speed and feed.

