



## List 5310 - EXOCARB® MAX-MINI FHL-GDTS

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

Work Material	Hardened Steel, Pre-Hardened Steels			Tool Steels H13, D2			Stainless Steels 440		
Drilling Speed	130-160 SFM			110-150 SFM			100-130 SFM		
Drill Dia. mm	Speed RPM	Feed IPR	Pecking (In)	Speed RPM	Feed IPR	Pecking (In)	Speed RPM	Feed IPR	Pecking (In)
1.0	14,000	0.0008-0.0020	0.0008-0.0020	13,000	0.0008-0.0020	0.0008-0.0020	11,000	0.0008-0.0020	0.0008-0.0020
1.1	13,000	0.0008-0.0020	0.0008-0.0020	12,000	0.0008-0.0020	0.0008-0.0020	10,000	0.0008-0.0020	0.0008-0.0020
1.2	12,000	0.0008-0.0020	0.0008-0.0020	11,000	0.0008-0.0020	0.0008-0.0020	9,000	0.0008-0.0020	0.0008-0.0020
1.3	11,000	0.0008-0.0020	0.0008-0.0020	10,000	0.0008-0.0020	0.0008-0.0020	8,600	0.0008-0.0020	0.0008-0.0020
1.4	10,000	0.0008-0.0020	0.0008-0.0020	9,000	0.0008-0.0020	0.0008-0.0020	8,000	0.0008-0.0020	0.0008-0.0020
1.5	9,500	0.0008-0.0020	0.0008-0.0020	8,500	0.0008-0.0020	0.0008-0.0020	7,400	0.0008-0.0020	0.0008-0.0020
1.6	9,000	0.0008-0.0020	0.0008-0.0020	8,000	0.0008-0.0020	0.0008-0.0020	7,000	0.0008-0.0020	0.0008-0.0020
1.7	8,400	0.0008-0.0020	0.0008-0.0020	7,500	0.0008-0.0020	0.0008-0.0020	6,600	0.0008-0.0020	0.0008-0.0020
1.8	8,000	0.0008-0.0020	0.0008-0.0020	7,100	0.0008-0.0020	0.0008-0.0020	6,200	0.0008-0.0020	0.0008-0.0020
1.9	7,500	0.0008-0.0020	0.0008-0.0020	6,700	0.0008-0.0020	0.0008-0.0020	5,900	0.0008-0.0020	0.0008-0.0020
2.0	7,200	0.0008-0.0020	0.0008-0.0020	6,400	0.0008-0.0020	0.0008-0.0020	5,600	0.0008-0.0020	0.0008-0.0020
2.5	5,700	0.0008-0.0020	0.0008-0.0020	5,100	0.0008-0.0020	0.0008-0.0020	4,500	0.0008-0.0020	0.0008-0.0020
3.0	4,800	0.0008-0.0020	0.0008-0.0020	4,200	0.0008-0.0020	0.0008-0.0020	3,700	0.0008-0.0020	0.0008-0.0020

1. Please use in a machine with precise spindle rotation. Tight clamping is critical.
2. The indicated speeds and feeds are for drilling with water-soluble fluid.
3. Please use water-soluble high density fluid (less than 20 times dilution).
4. We recommend the pilot hole operation prior to EXOCARB® MAX-MINI (List 5310).
5. The run out with a drill in the spindle should be less than 0.0001".
6. OSG's Shrink Fit System is the recommended tool holder for these drills.

For machines that cannot achieve the speeds indicated in the above table, please set rotation as high as possible. Tool life may be decreased.

