



**List 52510 & 78321 - PHOENIX® PZAG**  
**List 52511 & 78421 - PHOENIX® PZAG Bore**

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

	Work Material	Tensile Strength - Hardness	Drilling Speed Vc (SFM)	Feed Rate f (in/rev)				
				Ø0.531-0.625 (14-17.5mm)	Ø0.719-0.906 (20-23mm)	Ø1.000-1.813 (26-48mm)	Ø2.000-2.750 (54-72mm)	Ø3.000-0.313 (76-82mm)
P	Mild Steels, Carbon Steels (1010, 1018)	~180 HB	525 (330 - 655)	0.0055 (0.003-0.008)	0.007 (0.004-0.010)	0.008 (0.005-0.012)	0.016 (0.008-0.024)	0.016 (0.008-0.024)
	Carbon Steels, Alloy Steels (1050, 4140)	~280 HB	495 (330 - 655)	0.0055 (0.003-0.008)	0.007 (0.004-0.010)	0.008 (0.005-0.012)	0.016 (0.008-0.024)	0.016 (0.008-0.024)
	Die Steels (H13, D2)	~280 HB	395 (265 - 590)	0.005 (0.003-0.006)	0.0055 (0.004-0.008)	0.007 (0.005-0.010)	0.016 (0.008-0.020)	0.016 (0.008-0.020)
M	Stainless Steels (304, 420)	~250 HB	425 (265 - 590)	0.004 (0.003-0.006)	0.005 (0.004-0.008)	0.006 (0.005-0.010)	0.014 (0.008-0.020)	0.014 (0.008-0.020)
K	Cast Iron (No. 35 B)	~350 N/mm <sup>2</sup>	655 (495 - 915)	0.006 (0.003-0.010)	0.008 (0.004-0.012)	0.012 (0.006-0.016)	0.024 (0.012-0.032)	0.024 (0.012-0.032)
	Ductile Cast Iron (60-40-18)	~800 N/mm <sup>2</sup>	525 (330 - 720)	0.0055 (0.003-0.008)	0.007 (0.004-0.010)	0.008 (0.006-0.012)	0.016 (0.012-0.032)	0.016 (0.012-0.032)
N	Aluminum Alloys (6061, 7075)	~13% Si	650 (330 - 2625)	0.006 (0.003-0.010)	0.008 (0.004-0.012)	0.012 (0.006-0.016)	0.024 (0.012-0.031)	0.024 (0.012-0.031)
S	Heat Resistant Alloys (Inconel 718)	-	165 (100 - 200)	0.003 (0.002-0.0055)	0.003 (0.0024-0.0055)	0.005 (0.003-0.008)	0.010 (0.006-0.016)	0.010 (0.006-0.016)
	Titanium Alloy (Ti-6Al-4V)	-	200 (100 - 330)	0.003 (0.002-0.0055)	0.004 (0.0024-0.006)	0.0055 (0.003-0.008)	0.012 (0.006-0.020)	0.012 (0.006-0.020)
H	Pre-hardened Steel (P20, Stavax)	40 - 43 Hrc	330 (200 - 400)	0.003 (0.002-0.0055)	0.004 (0.0024-0.006)	0.0055 (0.003-0.008)	0.012 (0.006-0.020)	0.012 (0.006-0.020)
	Die Cast Steels (A2, S7)	43 - 48 Hrc	260 (165 - 330)	0.003 (0.002-0.0055)	0.003 (0.0024-0.0055)	0.005 (0.003-0.008)	0.010 (0.006-0.016)	0.010 (0.006-0.016)
	Hardened Steels (D2)	50 - 55 Hrc	200 (130 - 260)	0.003 (0.002-0.0055)	0.003 (0.002-0.0055)	0.005 (0.003-0.008)	0.010 (0.006-0.016)	0.010 (0.006-0.016)

