


List 8675

A BRAND AE-CR-TS-N, 3 Flutes, Regular Length, Reduced Neck, Corner Radius

A	SPEED FEED 21-23	CARBIDE	DLC	3 FLUTE	~40°		SHRINK FIT	REG	PACKED 1 PIECE
	Cutting Diameter Tolerance								

1/8" ≤ D ≤ 1"	0 / -0.0008"
---------------	--------------



EDP Number	Diameter	Corner Radius	Length of Cut	Neck Length	Neck Diameter	Overall Length	Shank Diameter
86750009	1/8	0.010	0.188	0.375	0.118	1.500	0.125
86750109	1/8	0.015	0.188	0.375	0.118	1.500	0.125
86750209	3/16	0.015	0.281	0.563	0.176	2.000	0.188
86750309	3/16	0.020	0.281	0.563	0.176	2.000	0.188
86750409	3/16	0.030	0.281	0.563	0.176	2.000	0.188
86750509	1/4	0.015	0.375	0.750	0.235	2.500	0.250
86750609	1/4	0.020	0.375	0.750	0.235	2.500	0.250
86750709	1/4	0.030	0.375	0.750	0.235	2.500	0.250
86750809	1/4	0.060	0.375	0.750	0.235	2.500	0.250
86750909	5/16	0.015	0.469	0.938	0.295	2.500	0.313
86751009	5/16	0.020	0.469	0.938	0.295	2.500	0.313
86751109	5/16	0.030	0.469	0.938	0.295	2.500	0.313
86751209	3/8	0.015	0.563	1.125	0.353	3.000	0.375
86751309	3/8	0.020	0.563	1.125	0.353	3.000	0.375
86751409	3/8	0.030	0.563	1.125	0.353	3.000	0.375
86751509	3/8	0.060	0.563	1.125	0.353	3.000	0.375
86751609	1/2	0.015	0.750	1.500	0.470	4.000	0.500
86751709	1/2	0.020	0.750	1.500	0.470	4.000	0.500
86751809	1/2	0.030	0.750	1.500	0.470	4.000	0.500
86751909	1/2	0.060	0.750	1.500	0.470	4.000	0.500
86752009	5/8	0.015	0.938	1.875	0.588	5.000	0.625
86752109	5/8	0.030	0.938	1.875	0.588	5.000	0.625
86752209	5/8	0.060	0.938	1.875	0.588	5.000	0.625
86752309	5/8	0.090	0.938	1.875	0.588	5.000	0.625
86752409	3/4	0.015	1.125	2.250	0.705	5.000	0.750
86752509	3/4	0.030	1.125	2.250	0.705	5.000	0.750
86752609	3/4	0.060	1.125	2.250	0.705	5.000	0.750
86752709	3/4	0.090	1.125	2.250	0.705	5.000	0.750
86752809	3/4	0.120	1.125	2.250	0.705	5.000	0.750
86752909	1	0.015	1.500	3.000	0.940	6.000	1.000
86753009	1	0.030	1.500	3.000	0.940	6.000	1.000
86753109	1	0.060	1.500	3.000	0.940	6.000	1.000
86753209	1	0.090	1.500	3.000	0.940	6.000	1.000
86753309	1	0.120	1.500	3.000	0.940	6.000	1.000

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High			300	400	17-4 PH	6061	Casting	Inconel			6Al4V	~35 HRC	35-45 HRC	45-50 HRC
1010	1035	1065	4140													
1018	1045		4340													

○ Good ⊙ Best

