


List 78PSF

PACKED 10 PIECE

OSG PHOENIX® PSF INSERTS









EDP Numbe	er	Designation	Number of Cutting		Grade				
			Edges	IC (mm)	T (mm)	α (°)	R (mm)	b (mm)	
7811076	•	SDHT09T308FR-NM	4	9.07	3.97	15°	0.8	2.5	CK010
7818076		SDHT09T308FR-NM	4	9.07	3.97	15°	0.8	2.5	XP4610

■ Stocked ▲ Globally Stocked ○ Made to Order; contact an OSG representative for details



PACKED 1 PIECE

List 78PFDC









*Outer diameter is 2 mm smaller than the DC when inserts are installed.

	EDP Number		Designation	Number of Cutting Edges		Grade				
			2003		AxB (mm)	T (mm)	α (°)	C (mm)	b (mm)	
	7841626		SDHW09T3AZFR	1	9.2 x 9.07	3.97	10°	0.5	3	DM001

Stocked Globally Stocked Made to Order; contact an OSG representative for details
Inserts may show discoloration, but it does not affect performance. The appearance of single crystal diamond may vary, but it does not affect performance.
Install SDHW09T3AZFR in only one flute. For all other insert slots, be sure to install SDHT09T308FR-NM inserts for balancing.



DESIGNATION EXPLANATION S D K T 09 T3 08 S R-GL XP3035 Clearance Tolerance Cutting Cutting Cutting Chip Insert Insert Thickness Corner Grade Radius Shape Features Edge Breaker Length Туре

In sout Cuarla	Chip	Coolant	P	M	K	N	S	Н
Insert Grade	Breaker		Steel	Stainless Steel	Cast Iron	Non-Ferrous	HRSA	Hardened Steel
CK010	NM	Υ				0		
XP4610	NM	N						
XP4610	NM	Υ						
DM001	NM	Υ						

NM:Aluminum

 \bigcirc Good

