

List 3430

EXOCARB® WXL-EBM



NEW

SPEED
FEED
7

CARBIDE

WXL

4 FLUTE

30°



SHANK
h6

STUB

REG

PACKED
1 PIECE



Radius Tolerance	
1/8" ≤ D < 1/4"	+/- .00027"
1/4" ≤ D	+/- .00039"

EDP Number		Mill Diameter		Length of Cut	Overall Length	Shank Diameter
		D (Inch)	Lc (Inch)	L (Inch)	d (Inch)	
34300023	●	1/8	0.250	2.000	0.125	
34300123	●	3/16	0.375	2.500	0.188	
34300223	●	1/4	0.500	3.500	0.250	
34300323	●	5/16	0.625	4.000	0.313	
34300423	●	3/8	0.750	4.000	0.375	
34300523	●	1/2	0.875	4.375	0.500	

● Stocked ▲ Globally Stocked ○ Made to Order; contact an OSG representative for details

HTE

P					M			K	N		S	H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High							6061	Casting	Inconel	6Al4V (30 HRC)				
1010	1035		4140	Die Steel	300	400	17-4 PH		6061 7075				~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
1018	1045	1065	4340													
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

