


List 16506

A BRAND A-SFT-LH, DIN Overall Length, Left Hand



EDP Number		Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Dia.	Square Width	Square Length
				L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	Ik (Inch)
1650601108	●	No. 10-24 UNC	H3	2.756	0.326	0.976	0.194	0.152	0.250
1650601208	●	No. 10-32 UNF	H3	2.756	0.326	0.976	0.194	0.152	0.250
1650601608	●	1/4-20 UNC	H5	3.150	0.397	1.177	0.255	0.191	0.313
1650601808	●	1/4-28 UNF	H4	3.150	0.397	1.177	0.255	0.191	0.313
1650602008	●	5/16-18 UNC	H5	3.543	0.444	1.377	0.318	0.238	0.375
1650602208	●	5/16-24 UNF	H4	3.543	0.444	1.377	0.318	0.238	0.375
1650602408	●	3/8-16 UNC	H5	3.937	0.500	1.535	0.381	0.286	0.438
1650602608	●	3/8-24 UNF	H4	3.543	0.500	1.377	0.381	0.286	0.438
1650602808	●	7/16-14 UNC	H5	3.937	0.570	1.712	0.323	0.242	0.406
1650603008	●	7/16-20 UNF	H5	3.937	0.570	1.712	0.323	0.242	0.406
1650603208	●	1/2-13 UNC	H5	4.331	0.614	1.933	0.367	0.275	0.438
1650603408	●	1/2-20 UNF	H5	3.937	0.614	1.933	0.367	0.275	0.438
1650603608	●	9/16-12 UNC	H5	4.331	0.665	1.972	0.429	0.322	0.500
1650603808	●	9/16-18 UNF	H5	3.937	0.665	1.972	0.429	0.322	0.500
1650604008	●	5/8-11 UNC	H5	4.331	0.728	2.125	0.480	0.360	0.563
1650604208	●	5/8-18 UNF	H5	3.937	0.728	2.125	0.480	0.360	0.563
1650604408	●	3/4-10 UNC	H5	4.921	1.000	2.433	0.590	0.442	0.688
1650604608	●	3/4-16 UNF	H5	4.331	1.000	2.433	0.590	0.442	0.688

● Stocked ▲ Globally Stocked ○ Made to Order; contact an OSG representative for details

P					M			K	N		S	H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High														
1010	1035	1065	4140	Die Steel	300	400	17-4 PH		6061	Casting	Inconel	6Al4V	~35	35-45	45-50	50-70
1018	1045	1065	4340						7075				(30 HRC)	HRC	HRC	HRC
⊙	⊙	⊙	⊙	○	⊙	⊙	⊙	○	○	○		⊙				
80-120 SFM	80-120 SFM	80-120 SFM	35-50 SFM	20-40 SFM	15-35 SFM	15-35 SFM	15-25 SFM	50-80 SFM	70-120 SFM	70-120 SFM			30-55 SFM			

○ Good ○ Best